



MERL, INC.
P. O. BOX 188
1777 NORTH COLONY ROAD
MERIDEN, CT 06450
P:203-237-8811

Installation Instructions for MERL Inc.
Battery Pack: P/N BP-1010

INSTRUCTIONS FOR THE REPLACEMENT OF BP-1010 BATTERY PACK

TO SEPARATE:

1. Put ON-OFF-ARM Switch in the OFF position.
2. Remove the ELT and Battery Pack from the mount.
3. Pull the Portable Antenna to the UP position
4. Remove the four (4) screws that hold the Transmitter to the Battery Pack and separate the two.
5. Disconnect the Battery Pack wiring by pulling the Snap Connector away from the bottom of the Printed Circuit Board mating connectors.

TO REASSEMBLE:

6. Connect the Battery Pack Snap Connector to the mating Connectors on the bottom of the Printed Circuit Board
7. Place the Transmitter into the Battery Pack, (do not pinch wires) and replace the four (4) screws that were removed in step #4, above. If the four holes do not align, turn the Battery Pack 180 degrees and re-insert.
8. Place the Portable Antenna into its stowed position.
9. If applicable:
 - a. Reconnect the Co-Axial Cable (leading to the External ELT Antenna) to the mating connector on the front of the Transmitter.
 - b. Re-Insert the separator between the antenna contact and the Portable Antenna.
 - c. If a Remote Control is used, re-connect the leads to the Transmitter
10. Push "G" Switch reset button and turn switch to ARM.

CAUTION- DO NOT DISPOSE OF EXPIRED BATTERY PACK IN THE FIRE!!!!